

University of Tasmania Open Access Repository

Cover sheet

Title

CORSnet-NSW Adjustable Antenna Mount (CAAM) for GNSS CORS

Author

Commins, R, Janssen, V

Bibliographic citation

Commins, R; Janssen, V (2012). CORSnet-NSW Adjustable Antenna Mount (CAAM) for GNSS CORS. University Of Tasmania. Conference contribution.

https://figshare.utas.edu.au/articles/conference_contribution/CORSnet-NSW_Adjustable_Antenna_Mount_CAAM_for_GNSS_CORS/23138996

Is published in:

Copyright information

This version of work is made accessible in the repository with the permission of the copyright holder/s under the following,

Licence.

Rights statement: Copyright 2012 IGS

If you believe that this work infringes copyright, please email details to: oa.repository@utas.edu.au

Downloaded from University of Tasmania Open Access Repository

Please do not remove this coversheet as it contains citation and copyright information.

University of Tasmania Open Access Repository

Library and Cultural Collections

University of Tasmania

Private Bag 3

Hobart, TAS 7005 Australia

E oa.repository@utas.edu.au

CRICOS Provider Code 00586B | ABN 30 764 374 782

utas.edu.au



IGS Workshop 2012, Olsztyn, Poland
July 23-27, 2012

Session P4 – Infrastructure and Data Centers
Poster P04-03

CORSnet-NSW Adjustable Antenna Mount (CAAM) for GNSS CORS

Russell Commins and Volker Janssen

Survey Infrastructure and Geodesy, NSW Land and Property Information, Bathurst, Australia

Russell.Commins@lpi.nsw.gov.au Volker.Janssen@lpi.nsw.gov.au

Abstract

Global Navigation Satellite System (GNSS) Continuously Operating Reference Station (CORS) networks are being built and expanded around the world, contributing to the definition and realisation of geodetic reference frames as well as providing reliable and accurate positioning infrastructure for a wide range of applications. Depending on the purpose of the GNSS station, CORS antenna monuments vary from concrete pillars anchored to bedrock to masts attached to buildings. An antenna mount is then used to connect the GNSS antenna to the monument. In all cases it is desired to orient the CORS antenna to True North in order to gain maximum benefit from GNSS antenna modelling. Other requirements generally include the unambiguous definition of the survey mark below the antenna (supporting a clear definition of the Antenna Reference Point, ARP), a zero or minimal antenna height above the monument, and the use of a truly vertical 5/8th Whitworth thread spigot. This poster introduces the CORSnet-NSW Adjustable Antenna Mount (CAAM), developed by NSW Land and Property Information (LPI) for CORSnet-NSW, LPI's rapidly growing GNSS CORS network covering the state of New South Wales, Australia. The CAAM was purposely designed to be incorporated into (rather than simply attached to) antenna masts located on buildings or free-standing pole monuments but can also be used for pillar monuments. Being free of removable parts, it is adjustable in order to orient the antenna to True North without introducing an antenna height, thereby allowing a clear definition and maximum traceability of the survey mark and the ARP.